




LED PROFIELN	Lengte	Lumen	Vermogen	Code	Prijs,€
SNITE LED	310 mm	358 lm	4,0 W	6349-1004	17,00
	539 mm	623 lm	7,0 W	6349-1007	22,00
LED opbouwprofiel incl. bevestigingsclips met geïntegreerde ministekker.	571 mm	660 lm	9,0 W	6349-1009	23,00
	871 mm	1006 lm	13,0 W	6349-1013	31,00
	1171 mm	1353 lm	18,0 W	6349-1018	37,00
	1471 mm	1699 lm	22,0 W	6349-1022	45,00

PowerLED
EEL: A+
Lichttemperatuur: 4000° K
Uitvoering: wit
Spanning: 220-240 V

Extra te bestellen	
Aansluitkabel 2000 mm	6349-1090 4,90
Optie	
Verbindingskabel 300 mm	6349-1093 2,50
Verbindingskabel 500 mm	6349-1095 3,50
Verbindingskabel 1000 mm	6349-1096 4,50

L=539 mm



Lumen
945

Lm/W
105

CRI
>80



LED PROFIELN	Lengte	° Kelvin	Lumen	Vermogen	Code	Prijs,€
LINEA LED	277 mm	3000° K	300 lm	4,0 W	6348-2204	16,00
	505 mm	3000° K	550 lm	7,0 W	6348-2207	19,00
LED opbouwprofiel met schakelaar incl. aansluitkabel 180 cm,	538 mm	3000° K	720 lm	9,0 W	6348-2209	21,00
	838 mm	3000° K	1050 lm	13,0 W	6348-2213	28,00
	1138 mm	3000° K	1550 lm	18,0 W	6348-2218	34,00
	277 mm	4000° K	300 lm	4,0 W	6348-2104	16,00
verbindingskabel, connector en bevestigingsclips.	505 mm	4000° K	550 lm	7,0 W	6348-2107	19,00
	538 mm	4000° K	720 lm	9,0 W	6348-2109	21,00
	838 mm	4000° K	1050 lm	13,0 W	6348-2113	28,00
	1138 mm	4000° K	1550 lm	18,0 W	6348-2118	34,00

EEL: A+
Uitvoering: wit
Spanning: 230 V

Optie	
Verbindingskabel 300 mm	6348-2293 1,30
Verbindingskabel 500 mm	6348-2295 1,60
Verbindingskabel 1000 mm	6348-2299 2,50

