

Product data sheet

TS 5000

Overhead door closer with guide rail for single-leaf doors with a leaf width up to 1400 mm



Product features

Closing force of EN2-6 with variable adjustment
Can be used for right and left hand doors without conversion
Hydraulic latching action which accelerates the door shortly before the closed position
Closing speed can be individually adjusted
Integrated back check, slows down doors that are thrown open forcefully
Visual closing force display for easy control of the setting
All functions can be adjusted from the front

Application Areas

Fire and smoke protection doors
Right and left single-action doors
Single-action doors up to 1400 mm leaf width
Door leaf installation hinge side and transom installation opposite hinge side

Product Data Table

Productname	TS 5000
Closing force in accordance with EN 1154	Yes, stepless 2 3 4 5 6
Leaf width (max.)	1400 mm
Suitability for fire protection doors	Yes
Adjustable closing force	Yes, stepless
Adjustable closing speed	Yes
Adjustable latching action	Yes, via valve
Integrated back check	Yes, hydraulically adjustable
Position of closing force adjustment	Front
Visual closing force display	Yes
Hold-open device	Optional

Accessory

Product name

Mechanical hold-open unit
Flexible opening restrictor
Cover cap door closer

Part

Product name

Guide rail TS 3/5000 vertically adjustable

Guide rail TS 3/TS 5000

TS 5000 door closer

T-Stop guide rail TS 3/5000